









## Shears shears

Order code	Tip	(Ø mm)	(awg)	Weight (gr)	Length (mm)	Esd code	Notes
CS 30		1.30	16	80	144	CS 30 D	shears



















## Wire strippers

Order code	Tip	(Ø mm)	(awg)	Weight (gr)	Length (mm)	Esd code	Notes
SF 30		0.20÷0.64	32-22	78	141	SF 30 D	adjustable wire stripper fixed wire
SFF 30		0.32÷0.51	28-24	76	141	SFF 30 D	stripper

## Multi-use shears

Order code	Tip	(Ø mm)	(awg)	Weight (gr)	Length (mm)	Esd code	Notes
CSF 30		s0.4÷c1.3	26-18	80	144	CSF 30 D	shears and wire strippe
CSP 30/1		0.25÷0.81	30-20	102	165	CSP 30/1 D	shears, wire stripper and pliers
CSP 30/2		0.81÷2.59	20-10	102	165	CSP 30/2 D	shears, wire stripper and pliers

## การสั่งซื้อพิเศษ (More special Ordering Information)

Order code	Tip	(Ø mm)	(awg)	Weight (gr)	Length (mm)	Esd code	Notes
CS 30 L		1.30	16	72	152	CS 30 L D	shears
CSO 30		1.63	14	72	148	CSO 30 D	shears
CS 30 X		1.63	14	72	150	CS 30 X D	shears and Pliers
CS 30 XZ		1.63	14	72	150	CS 30 XZ D	shears for soldering iron tips
CSF 30 S		0.4÷1.0	26-18	84	144	CSF 30 S D	shears /adjustable wire stripper
CSP 30/ 3		max 10	000	102	165	CSP 30/ 3 D	cable cutter pliers
CSP 30 G		-	-	110	155	CSP 30 G	rubber seals cutte
CSP 30 GL		-	-	110	165	CSP 30 GL D	rubber seals cutte
CSP 30 GR		-	-	110	155	CSP 30 GR D	rubber seals cutte
PST 0.5		0.5	24	33	125	-	pulling action wire stripper
PST 0.6		0.6	22	33	125	-	pulling action wire stripper
PST 0.8		0.8	20	33	125	-	pulling action wire stripper
PST 1.0		1.0	18	33	125	-	pulling action wire stripper
SF 40 1		0.25÷1.0	30-18	22	50x55	-	flat wire stripper
SF 40-2		1.30÷1.8	16-13	22	50x55	-	flat wire stripper
PCC 1		-	-	50	115	-	wire stripper for co-axial cables
PS 4÷10		4÷10/0.8÷2.6	6÷000/20÷10	50	115	-	wire stripper
PRF 0		0.8÷2.6	20÷10	50	115	-	wire scraper pliers




## Shears shears

### SC 30



**CS 30** : Easy to handle shears, designed for use in electronics but also used for the most desperate tasks.  
 Steel thickness 3.0 mm.




Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
CS 30	CS 30 D	1.30	16	80	144

## Wire strippers

### SF 30



**SF 30** : Pliers for Ø mm 0.20÷0.64 fitted with elastic part that enables the stripping of the insulating sleeve of cables without damaging the conductor wires.




Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
SF 30	SF 30 D	0.20÷0.64	32-22	78	141

### SFF 30



**SFF 30** : Fixed wire stripper for Ø mm 0.32÷0.51. Different cutting capacities to those shown are available.



Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
SFF 30	SFF 30 D	0.32÷0.51	28-24	76	141


## Multi-use shears

### CSF 30



**CSF 30** : Multi-use tool that can be used both as shears (Ø 1.3mm-16 AWG) and wire strippers (Ø 0.4mm-26 AWG).

\*w: wire diameter for wire stripper function;  
 s\* wire diameter for shears function




Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
CSF 30	CSP 30 D	s0.4÷c1.3*	16	80	144

### CSP 30/1



**CSP 30/1** : Very strong multi-use tool. It can be used as: Shears, Multi-diameter Wire stripper, pliers




Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
CSP 30/1	CSP 30/1 D	0.25÷0.81	30-20	102	165

### CSP 30/2



**CSP 30/2** : Very strong multi-use tool. It can be used as: Shears, Multi-diameter Wire stripper, pliers.



Order Code	ESD code	(Ø mm)	awg	Weight (gr)	Length (mm)
CSP 30/2	CSP 30/2 D	0.81÷2.59	20-10	102	165